

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 827 108 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
04.03.1998 Bulletin 1998/10

(51) Int. Cl.⁶: G06K 19/07

(21) Application number: 97115012.3

(22) Date of filing: 29.08.1997

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE

(72) Inventor: Sakashita, Hitoshi
Misato-shi, Saitama (JP)

(30) Priority: 30.08.1996 JP 230342/96
28.08.1997 JP 232630/97

(74) Representative:
VOSSIUS & PARTNER
Postfach 86 07 67
81634 München (DE)

(71) Applicant: LINTEC Corporation
Tokyo (JP)

(54) Non-contact type data carrier label

(57) A non-contact type data carrier label (1) has a data carrier (5) for storing information and a support member (3) for holding the data carrier (5), and it is able to attach to a product. The support member (3) has a holding portion for holding the data carrier (5) and paste portion to be pasted on the product in a attach-

ble/detachable manner. A releasable type adhesive layer (2) is formed on the support member. Thus, the data carrier label (1) can be attached to and detached from the product more easily compared with that of conventional one.




FIG. 2

EP 0 827 108 A2

Description

The present invention relates to a reusable non-contact type data carrier label.

For recognizing products in physical distribution systems, visitors to a specific place, or the like, heretofore, automatic recognition or identification technologies such as data carrier, bar code, magnetic stripe, optical character recognition, visual recognition, and voice recognition have been known. Among those technologies, the bar code and the magnetic stripe have been used in general. However, each of them has only a function of bringing an entity corresponding to information, so that the amount of information is comparatively small. In addition, these devices are prepared on the basis of information which is previously decided. It means that only the information without any alterations is expressed as a bar code. If the information is altered after attaching the bar code on the product, there is the need to change the bar code label with new one.

In recent years, therefore, attention is being given to the data carrier technology because it is much different from the other types in that the data carrier is not only readable but also writable to add new data without contact.

Hereinafter, one of the examples of how to use the data carrier will be described.

A physical distribution system performs activities of such as transferring, storing, and assorting products (merchandise) and controls the information concerned about these activities. In this case, there is the need for transferring both products and information. Therefore, for example, the data carrier may be used as follows when a plurality of containers is shipped from a distribution center A to a distribution center B.

(1) A main control center sends information to a computer of the distribution center A. The information concerns about work instructions of individual data such as trade name, number, address, and container's number, and so on.

(2) Then, necessary information is written on the data carrier through a writing device, and hence the written information is stored in the data carrier.

(3) The written data carrier is attached to the corresponding container. A holding means is required for attaching the data carrier to the container, for example, as shown in Fig. 1, the data carrier 100 is attached on a predetermined position on the container by means of screw. In the figure, the reference numeral 101 denotes a data carrier, 102 denotes a supporting plate, 103 denotes a screw as the holding means, and 104 denotes a container.

(4) A data carrier reading/writing device reads the information stored in the data carrier attached on each container. The containers are assorted and shipped in accordance with the read information that includes their merchandises, shipping

addresses, trade names, and the like. Simultaneously, the read information is automatically entered into a computer through the data carrier reading/writing device and then transmitted to a host computer of the main control center through a data communicating system.

(5) When the containers have arrived on a distribution center B, a data carrier reading/writing device reads the information stored in the data carrier attached on each container. Simultaneously, the read information is automatically entered into a computer through the data carrier reading/writing device and then transmitted to a host computer of the main control center through a data communicating system.

Consequently, using the data carrier allows the online physical distribution management in real time with great accuracy.

For detaching the data carrier from the container, an operator has to take off a member that holds the data carrier by using a tool or the like. Generally, the operator must prepare tools for attaching and detaching the data carriers, and have to deal with a lot of containers, so that the process of attaching and detaching the data carriers by using the tool is a time-consuming job and one of the factors interfering the speedy distribution. To solve this disadvantage, there is an idea of imbedding the data carrier in the container. However, it complicates the process of manufacturing the container, causing another problem to be solved.

Accordingly, an object of the present invention is to provide non-contact type data carrier label which can be easily attached and detached.

There is provided a non-contact type data carrier label to be attached to a product, having a data carrier for storing information and a support member for holding the data carrier, wherein the support member comprises: a holding portion for holding the data carrier; and a paste portion to be pasted on the product in an attachable/detachable manner, on which a releasable type adhesive layer is formed.

Here, the holding portion may be provided as one surface of the support member, while the paste portion is provided as other surface of the support member.

The holding portion and the paste portion may be provided on one surface of the support member.

The releasable type adhesive layer may be made of a weak adherent pressure-sensitive adhesive.

The releasable type adhesive layer may be made of a water soluble adhesive.

A state adhesive strength of the releasable type adhesive layer may be 350 g/cm or less.

The data carrier may be selected from types of an electromagnetic induction, electromagnetic coupling, radiomagnetic communication, and micro wave communication.

The releasable type adhesive layer may be made of

a water soluble pressure-sensitive adhesive.

The above and other objects, effects, features and advantages of the present invention will become more apparent from the following description of embodiments thereof taken in conjunction with the accompanying drawings.

Fig. 1 is a schematic side view of the conventional data carrier label in the type of non-contact;

Fig. 2 is a schematic side view of the non-contact type data carrier label as one of the preferred embodiments of the present invention;

Fig. 3 is a schematic plane view of the non-contact type data carrier label as one of the preferred embodiments of the present invention;

Fig. 4 is a schematic side view of the non-contact type data carrier label as one of the preferred embodiments of the present invention;

Fig. 5 is a schematic plane view of the non-contact type data carrier label as one of the preferred embodiments of the present invention;

Fig. 6 is a schematic side view of the non-contact type data carrier label as one of the preferred embodiments of the present invention;

Fig. 7 is a schematic plane view of the non-contact type data carrier label as one of the preferred embodiments of the present invention; and

Fig. 8 is a schematic side view of a contacted portion between a supporting film of the non-contact type data carrier label and the object.

Embodiment 1

Fig. 2 and Fig. 3 show a non-contact type data carrier label as one of the preferred embodiments of the present invention, where Fig. 2 is a side view and Fig. 3 is a plane view thereof.

As shown in the figures, the non-contact type data carrier label 1 comprises a supporting film 3, a data carrier 5, and a flap 6. The supporting film 3 is provided as a support member having a pasting portion on which an adhesive agent as a releasable type adhesive layer 2 is applied and holding portion on which the data carrier 5 is stacked and fixed through a non-releasable type adhesive layer 4. Furthermore, the flap 6 is arranged on one longitudinal directional end of the supporting film 3.

A raw material of the supporting film may be the one showing the excellent properties of thermal resistance, drug resistance, water resistance, weathering resistance, and so on. For example, the raw material can be selected from polyester resin, polyvinyl chloride resin, polyurethane resin, and the like.

The adhesive agent being applied on the supporting film 3 forms the releasable type adhesive layer that allows the repeated use of the data carrier label. That is, it is easily peeled off from an object 7 (e.g., a container) by pulling the flap 6 in the direction of arrow A. The adhesive layer 2 may be provided as in the form of an

adhesive tape. Furthermore, various kinds of adhesives may be used as the releasable type adhesive layer 2. Among them, preferable adhesives for releasable type adhesive layer 2 are a weak adherent pressure-sensitive adhesive and releasable type pressure-sensitive adhesive, which are well known in the art, for example natural rubbers, synthetic rubbers, acrylate resins, polyvinyl ether resins, and silicon resins. Concrete examples of the synthetic resins include: styrene-butadiene rubber, polyisobutylene rubber, isobutylene-isoprene rubber, isoprene rubber, styrene-isoprene block copolymer, styrene-butadiene block copolymer, styrene-ethylene-butylene copolymer, and ethylene-acetate vinyl thermoplastic elastomer. Concrete samples of the acrylate resins include: homopolymer or copolymer of acrylic acid, acrylic methyl, acrylic ethyl, acrylic propyl, acrylic butyl, acrylate-2-ethylhexyl, methacrylic ethyl, methacrylic butyl, and acrylonitrile. Concrete examples of polyvinylether resins include: polyvinylether, and polyvinyl isobutyle ether. Furthermore, concrete examples of the silicon resins include dimethyl polysiloxane. These adhesives may be used solely or used as a combination of at least two adhesives.

In addition, the adhesive strength of the above releasable type adhesive layer is 350 g/cm or less of state adhesive strength defined by JIS-Z1523. If it is over 350 g/cm, the peeling characteristics of the data carrier label 1 will be deteriorated (so-called picking destruction of the surface of the product).

In general, the data carrier 5 is of an electromagnetic induction type, electromagnetic coupling type, radiomagnetic communication type, or micro wave communication type, and comprises a printed circuit substrate that allows a radio data transmission. In the present embodiment, a card type data carrier having a transmission distance of 0.1 to several ten meter (e.g., Miocrostamp™ available from Micron Co., Ltd.) is used. This card is of electromagnetic coupling type and is able to read and write information. In addition, a memory capacity of this card is several ten byte to several kilo byte. If required, over one mega byte memory capacity can be provided.

Embodiment 2

Fig. 4 and Fig. 5 are a non-contact type data carrier as a second embodiment of the present invention, where Fig. 4 is a side view and Fig. 5 is a plane view thereof.

As shown in the figures, the non-contact type data carrier label 10 is configured as the same way as that of Embodiment 1 except the flap. That is, the non-contact type data carrier 10 of the present embodiment comprises a supporting film 13 and a data carrier 15. The supporting film 13 is provided as a support member having a pasting portion on which an adhesive agent as a releasable type adhesive layer 12 is applied and a holding portion on which the data carrier 15 is stacked

and fixed through a non-releasable type adhesive layer 14.

The adhesive agent being applied on the supporting film 13 forms the releasable type adhesive layer 12 which is easily able to peel off the data carrier label 10 from the object (e.g., a container) 17. In the first embodiment, the label 1 is peeled off by a force caused by pulling the flap 6. In this embodiment, however, a water-soluble adhesive agent used as the releasable type adhesive layer, so that the data carrier label can be easily peeled off from the object by dipping into water or an alkaline aqueous solution.

The water-soluble adhesive agent used in the present invention is an adhesive to be dissolved or swollen in water or an alkaline aqueous solution. In addition, the above water soluble adhesive agent may be a water-soluble pressure-sensitive adhesive that pastes the data carrier 10 on the object just after peeling its protective sheet (release liner).

The composition of water-soluble pressure-sensitive adhesive which is used in the releasable adhesive layer 12 may be a water-soluble adhesive prepared by adding a surface activating agent which is able to provide plasticity, into a copolymer obtained by a copolymerization between vinyl-based monomers having carboxylic functional group and the other vinyl-based monomers which are able to polymerize with the vinyl-based monomers with carboxylic functional group. In this case, the above surface activating agent may be selected from the group of nonionic surface active agent having ethylene oxide functional group, such as alkylaryl ether typed, for example polyoxyethylene nonylphenyl ether, polyoxyethylene octylphenyl ether, and the like, alkylether typed, for example polyoxyethylene lauryl ether, polyoxyethylene oleyl ether and the like, alkylester typed, for example, polyoxyethylene laurylate, polyoxyethylene oleate, sorbitan oleate, and the like, and alkylether phosphate ester, and compound having ethylene oxide/ propylene oxide block copolymer such as Pluronic and Tetronic (trade names, available from Asahi Denka Co., Ltd.).

Furthermore, anion-surface active agent having ethyleneoxy functional group may be used.

Embodiment 3

Referring now to Fig. 6 and Fig. 7, a non-contact type data carrier label as another preferred embodiment of the present invention will be described below.

As shown in the figures, the non-contact type data carrier label 20 comprises a supporting film 23 and a data carrier 25. The supporting film 23 is provided as a support member having a pasting portion on which an adhesive agent as a releasable type adhesive layer 22 is applied and a holding portion on which the data carrier 25 is stacked and held in the gap 28 formed on supporting film 23.

In the first and second embodiments, the data car-

rier is provided on the support film. In this embodiment, on the other hand, the non-contact type data carrier 20 has a support film 23 which is provided over a data carrier 25. That is, the supporting film 23 is formed in the shape of a comparatively thick rectangular body with a gap 28 formed as a rectangular recess. In this embodiment, furthermore, one of the releasable type adhesives of Embodiments 1 and 2 is applied on an edge 22 around the gap 28. A data carrier 25 is placed in the gap 28 formed as the rectangular recess. Then, an object 27 is covered with the supporting film 23 so as to contact the data carrier 25 with the object 27.

Embodiment 4

In the non-contact type data carrier label of one of the above first to third embodiments, the application of a releasable type adhesive on the supporting film is performed with consideration given to adhesive strength, easiness of peeling, and the like of the adhesive. A method of applying the adhesive on the supporting film may be of uniformly applying the adhesive on a whole surface of the supporting film, applying the adhesive as a plurality of stripes on a surface of the supporting film, applying the adhesive as a plurality of dots on a surface of the supporting film, applying the adhesive as a frame on a surface of the supporting film, or the like.

In this embodiment, the releasable type adhesive layer is a weak adherent pressure-sensitive adhesive including fine globular elastomeric polymer particles. As shown in Fig. 8, globular polymer particles 32 are positioned between a supporting film 33 and an object 37, so that a well-spaced gap 38 is formed between the particles to make the peeling more easy. For the polymer of the present embodiment, polyacrylic ester, natural rubber, SBR, polyisoprene, polybutadiene, styrene-butadiene-acrylic ester terpolymer, or the like may be used. In addition, an average particle diameter of the fine globular elastomeric copolymer is preferably in the range of 10 to 100 μm . Additional components except the fine globular elastomeric copolymer may be one or a mixture of at least two compound selected from acrylic ester, polyacrylic acid, SBR, styrene-acrylic ester copolymer, styrene-butadiene-acrylic ester terpolymer, polyvinyl acetate, gelatin, animal glue, casein, and so on.

In addition, the adhesive strength of the above weak adherent pressure-sensitive adhesive layer is 350 g/cm or less of state adhesive strength defined by JIS-Z1523. If it is over 350 g/cm, the peeling characteristics of the data carrier label 1 will be deteriorated.

As described above, therefore, the non-contact type data carrier label of the present invention comprises the support member having the releasable type adhesive layer, so that the data carrier label can be peeled from the object more easily compared with that of conventional one.

The present invention has been described in detail with respect to preferred embodiments, and it will now

be apparent from the foregoing to those skilled in the art that changes and modifications may be made without departing from the invention in its broader aspects, and it is the intention, therefore, in the appended claims to cover all such changes and modifications as fall within the true spirit of the invention.

Claims

1. A non-contact type data carrier label to be attached to a product, having a data carrier for storing information and a support member for holding said data carrier, characterized in that

said support member comprises:
a holding portion for holding said data carrier;
and
paste portion to be pasted on said product in a attachable/detachable manner, on which a releasable type adhesive layer is formed.

2. A non-contact type data carrier label as claimed in Claim 1, characterized in that

said holding portion is provided as one surface of said support member, while said paste portion is provided as other surface of said support member.

3. A non-contact type data carrier label as claimed in Claim 1, characterized in that

said holding portion and said paste portion are provided on one surface of said support member.

4. A non-contact type data carrier label as claimed in Claim 1, 2 or 3, characterized in that

said releasable type adhesive layer is made of a weak adherent pressure-sensitive adhesive.

5. A non-contact type data carrier label as claimed in Claim 1, 2, 3 or 4, characterized in that

said releasable type adhesive layer is made of a water soluble adhesive.

6. A non-contact type data carrier label as claimed in Claim 1, 2, 3, or 4, characterized in that

said releasable type adhesive layer is made of a water soluble pressure-sensitive adhesive.

7. A non-contact type data carrier label as claimed in any one of Claims 1 to 6, characterized in that

a state adhesive strength of said releasable

type adhesive layer is 350 g/cm or less.

8. A non-contact type data carrier label as claimed in any one of Claims 1 to 7, characterized in that

said data carrier is selected from types of an electromagnetic induction, electromagnetic coupling, radiomagnetic communication, and micro wave communication.




FIG. 1 (PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 827 108 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
19.05.1999 Bulletin 1999/20

(51) Int. Cl.⁶: **G06K 19/07**

(43) Date of publication A2:
04.03.1998 Bulletin 1998/10

(21) Application number: 97115012.3

(22) Date of filing: 29.08.1997

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE

(30) Priority: 30.08.1996 JP 230342/96
28.08.1997 JP 232630/97

(71) Applicant: LINTEC Corporation
Tokyo (JP)

(72) Inventor: Sakashita, Hitoshi
Misato-shi, Saitama (JP)

(74) Representative:
VOSSIUS & PARTNER
Postfach 86 07 67
81634 München (DE)

(54) Non-contact type data carrier label

(57) A non-contact type data carrier label (1) has a data carrier (5) for storing information and a support member (3) for holding the data carrier (5), and it is able to attach to a product. The support member (3) has a holding portion for holding the data carrier (5) and paste portion to be pasted on the product in a attachable/detachable manner. A releasable type adhesive layer (2) is formed on the support member. Thus, the data carrier label (1) can be attached to and detached from the product more easily compared with that of conventional one.




FIG. 2

EP 0 827 108 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 97 11 5012

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 5 142 270 A (ORTIZ LUIS F ET AL) 25 August 1992 * column 5, line 46 - line 65; figures 1-3 *	1-8	G06K19/07 G06K19/04 G06K19/077
X	EP 0 704 816 A (HUGHES IDENTIFICATION DEVICES) 3 April 1996 * column 4, line 25 - line 45; figure 2 *	1,2,8	
A	EP 0 220 056 A (UNITED MERCHANTS & MFG) 29 April 1987 * abstract * * page 6 - page 15; figures 1-3 *	1,4-7	
A	WO 93 12513 A (GUSTAFSON AKE) 24 June 1993 * abstract; figure 1 *	1,3	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			G06K
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 March 1999	Examiner Degraeve, A
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 11 5012

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-03-1999

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5142270	A	25-08-1992	AU 655645 B	05-01-1995
			AU 2009692 A	30-12-1992
			CA 2103355 A,C	23-11-1992
			EP 0587696 A	23-03-1994
			FI 935118 A	18-11-1993
			JP 7500432 T	12-01-1995
			MX 9202424 A	01-02-1993
			NO 934189 A	19-11-1993
			NZ 242809 A	22-12-1994
			WO 9221113 A	26-11-1992
			US 5241299 A	31-08-1993
EP 0704816	A	03-04-1996	US 5541399 A	30-07-1996
			JP 8242116 A	17-09-1996
EP 0220056	A	29-04-1987	US 4767654 A	30-08-1988
			AU 6388886 A	30-04-1987
			JP 62161185 A	17-07-1987
WO 9312513	A	24-06-1993	AT 136674 T	15-04-1996
			AU 3086392 A	19-07-1993
			BR 9206945 A	28-11-1995
			DE 69209851 D	15-05-1996
			DE 69209851 T	05-09-1996
			EP 0617826 A	05-10-1994
			ES 2086137 T	16-06-1996
			JP 6511579 T	22-12-1994

EPO FORM P0439

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82